MRI

COOPERATIVE EXTENSION WORK

IN

AGRICULTURE AND HOME ECONOMICS

STATE OF UTAH LOGAN

UTAH STATE AGRICULTURAL COLLEGE AND
U. S. DEPARTMENT OF AGRICULTURE
COOPERATING

EXTENSION SERVICE

July 15, 1948



Mr. Ray Thatcher County Agent Ranguitch, Utah

Dear Mr. Thatcher:

The following is a report of my trip to Boulder, July 6-10 together with recommendations as to changes and improvements in the handling of their irrigation water.

I arrived at Boulder at noon on July 6 and immediately started to study the very complicated system of water rights and exchange of water between different rights. I talked to practically every one there individually and in groups and after reading the McCarty decree and Garrison decree and subsequent applications for water and then talking to a representative of the State Engineer.

I have some recommendations to make which are not what I had intended to make but are based upon facts gotten from the State Engineer's office.

The situation is about as follows: Judge McCarty decreed 7/16 of Boulder Creek to certain users and 9/16 to other users but in a paragraph following says "and that in normal seasons there are 24 second feet of water in Boulder Creek". I found 36.36 c.f.s. in Boulder Creek on July 7. The primary users of Boulder Creek since 1901 have used not only the 24 c.f.s. but all waters flowing and generally up to July 1. This flow has been two or three times the amount specified by Judge McCarty.

In 1931 and again in 1945 the Boulder Irrigation and Development Co. filed on storage and high water for storage in Spectacle Lake Reservoir. Also sometime about 1945 this same company filed for 70 c.f.s. of high water. In 1947 these two applications (ie) storage of 1347.89 ac. ft. for Spectacle Lake Reservoir and 70 c.f.s. high water were re-filed for in the name of the State Water and Power Board. These two applications are numbered 19138 and 19139 and are in good standing in the State Engineers office.

The way the situation now stands is, the primary water was set by Judge McCarty at 24 c.f.s. in Boulder Creek, subsequent developments have further fixed this figure. The State Water and Power Board have loaned State money for completion of Spectacle Lake Reservoir and could not possibly, without due process of law, allow this figure to be changed.

My recommendations found later in this letter are based upon the above facts and even though I may have favored some other course I could not do otherwise than face these facts.

WATER MEASUREMENTS

Nineteen measurements of water were made over a period of 5 days. These measurements were mainly made with a current meter but several were made with standard measuring devices in good condition. Wherever there was a question about the reliability of the measuring device a current mater measurement was taken. The location of the measurements are shown on the attached sketch map which is made a part of this report but the recaputulation is repeated in the following table.

MEASUREMENT RECAPITULATION

Manber	Date	Amount	Reas	How Made
1	1/6/48	15.58 c.f.s.	Saw Mill	Current Mter
2	7/6/48	8,53 efe	E. Boulder	Current Mater
3	7/7/48	2,86 efe	Otto Hams	Current Motor
4	7/7/48	3.62 efe	Leland Hame	Current Motor
5	7/7/48	14,30 efs	Lower Canal	Parchall Flume 3' wide
6	7/7/48	2.65 efs	Lymon Deer Greek	Current meter
7	7/7/48	1.75 efs		h Parchall Flume 9" wide
8	7/8/46	7,29 efe	Peterson-Baker-Hoesen	
9	7/8/48	1.31 efs	Emeron Peterson & GLA	
10	7/7/48	1.54 efe	Loster Baker	18" L. Rec. Weir
11	7/8/48	1.43 efs	Burnell Baker	Current Meter
12	7/8/48	2,17 efs	Lester Mossessen	Current meter
13	7/8/48	1.45 efs	Lester Baker	18" Rectangular Weir
14	7/7/48	8.28 efe	King Ditch @ Cattle Go	
15	7/7/48	1.50 efe	E. Cocabe	9" Wide Parchall Flum
16	7/10/48	0,168fe	Town Ditch at School	"Y" Notch Heir
17	7/10/48	3.17 efs	•	2" Wide Parehall Flume
18	7/10/48	0.40 efe	Porest Service	Current motor
19	7/10/48	3,04 efs	John King	Current motor

It shows a total of 36.36 c.f.s. flowing in Boulder Greek and a total of 4.40 c.f.s. in Deer Greek.

CONTROL AND MEASURING DEVICES

Since the McCarty decree specified a definite portion of the stream to each user, the prevailing device for separating the water is a proportional divider. Most of those found were in poor condition and in no single instance was there one which was doing a satisfactory job. In general, proportional dividers have not proven satisfactory because the channel immediately above the divider becomes filled with silt and the velocity of approach becomes uneven and one side or the other gets the advantage. It is much more satisfactory to measure the two streams or knowing the entire amount measure one stream and then divide according to the rights.

Due to the anticipated use of storage water and distribution of high water according to shares of stock owned in the Spectical Lake Reservoir I strengly recommend the installation of measuring devices according to the table given below:

Number Refer to sketch map	Name or Location	Kind of device
	At head of East upper Boulder	3º Parchell Flume in upper canal 18º Dia. Calco meter Cate in main boulder Creek. This installation will require the installation of a flume with a fleed control gate above the entrace into Parchall Flume & Calco Meter gate. The flume should have spillway sides such that high water may spill into main channel and upper canal. In normal times all the unto would be measured in correct amounts through the Parchall Flume and Calco Meter gate but in case of a flood or during high water the flood gate being closed to predetermined amount the extra water would spill over each side of the flume and coul be divided proportionally between the cana and main stream.
1	George Armond	14" Calco Motor gate, 2' Rectangular Meir Removable crest bulkheed.
1	Saw Mill	2' Parshall Flume 24" Diameter Celco Meter gate With flood control as described at Head of East Upper Boulder Creek

In most instances alternative measuring devices have been recommended. Plans are attached hereto for a Bulkhead Weir with removable crest. Where there is sufficient fall this is a much less expensive device than either Calco Meter Gate or Parchall Flume and where the crest is removed after measuring or at intervals to allow for desilting it does a very satisfactory job of measuring.

All Parshall flumes now installed are without stilting wells. These wells should be installed in all flumes as a correct head is very difficult if not impossible to read without a well.

METHOD OF DELIVERY

Many very wasteful practices of water use were found in Boulder but probably the most wasteful is the use of too small streams. It is recommended that in every case where possible several individuals combine their streams and divide the time. It is recognised that in a very few instances due to location, etc. this method will not be feasable or practical but in most places several irrigators could combine and save much time and water.

GENERAL RECOMMENDATIONS

Up to the present time there has been no way to store water and since the high water was divided according to primary rights every user received nearly all the water he needed up to approximately July 1 and from that date the primary users took all the water. Another prevalent practice in the past has been for the individual user to adjust his own stream. While not in agreement with the dully appointed commissioner this very objectional method of handling is being followed at the present time.

The water laws of the state of Utah gives the State Engineer jurisdiction over the measurement, appropriation, apportionment and distribution of all water in the State. (See Title 100, chapter 2, sectional, Utah Code Annalated) The State Engineer has power to appoint a water commissioner over any stream or streams (100-5-1) who in turn has pelice powers (100-2-9).

Because the high water will be distributed according to the amount of water owned in the Speciale Lake Reservoir it is recommended that stock be purchased in the reservoir to the maximum amount allowed by the company which according to date secured from the Boulder Irrigation and Development Company is as follows:

Alvey, Arthur	400,00
Baker, C. V. est	3,200,00
Baker, Burnell	1,600.00
Goombs, E. H.	4,600.00
Cocabs, Kay	1,600.00
King, Clyde	800,00
King, John	3,200,00

King, Reed, est.	\$ 4,800.00
Hall, Horace	200.00
Hansen, Mrs. A. C.	400.00
Hansen, Franklin C.	1,800,00
Hansen, Jean D.	600.00
Hansen, Omer	400.00
Hansen, George	800,00
Hansen, Yern	1,600.00
Hame, Henry J.	1,600.00
Have, Leland	1,000,00
Lyman, Hasel	
Behumin, Max	3,200.00
	3,040.00
Mooman, Doyle	100.00
Moosman, Harvey	400,00
Moceman, Lorin	2,400.00
Mooman, Gries	200,00
Ormend, Gertrude	1,000.00
Ormand, Glam K.	800.00
Peterson, Resa	1,600,00
Peterson, Mm. (Estate)	1,600.00
Thatcher, R. A.	800.00
Thompson, J. R.	800.00

It is further recommended that in order to make a more compact and unified company all primary users turn over all rights, in the form of a quick claim deed, to the company in leiu thereof each person turning over such water right should receive a stock certificate. Of course, as soon as the Reservoir is completed their certificates should be issued on this stock. It is suggested that the company have a form printed (after consulting an attorney) for a quick claim deed so that all will be uniform and that as soon as these are signed over to the acapeany they be recorded in the county records.

There are several advantages in having stock certificates instead of the present decreed water: First, the water is now apurtanent to the land to which it was decreed and may not be moved without an application to the State Engineer, requesting a change in point of use. If a protest is made it may be impossible without court action to change the use to another point. If the stock is owned by a company it becomes the responsibility of the directors to grant transfers and settle other operational problems. Second, these stock certificates are more negociable. Third, the company can lawy assessments to enlarge ditches, install structures, clean ditches and in general do a better job of distribution and management than individual users.

A water commissioner for Boulder area should be appointed by the State Engineer, according to the State Water Law (100-5-1). This is dens after consultation with the users. In actual practice this means a recommendation comes from the users of a competent man and the State Engineer makes the appointment.

Mr. Ivan Lyman, present water master, is considered competent to make measurements on standard devices and in fact competent to install most of them and therefore, if he is agreeable to most of the users it is recommended his name be submitted to the State Engineer for appointment as Water Commissioner for this drainage area.

I am sure everyone in Boulder is desirous of getting a good operating procedure for their water. They were most ecoperative with me and I assure you it is my desire to do everything for the good of this community.

Thanks for your trip over to Boulder while I was there. I will be glad to help further on this problem if I can.

Yery truly yours

JAMES R. BARKER

Extension Irrigationist

Rher